

Adaptive Monitoring

Björn Weißenfels

11. Oktober 2012

Gliederung

- 1 Einleitung
 - Motivation
 - Ansatz
 - Syntax
- 2 ProbeController
 - API
 - ProbeController
- 3 Konfiguration über Datei
 - Kieker Properties
 - Konfigurationsdatei
- 4 Live Demo

Gliederung

- 1 **Einleitung**
 - Motivation
 - Ansatz
 - Syntax
- 2 ProbeController
 - API
 - ProbeController
- 3 Konfiguration über Datei
 - Kieker Properties
 - Konfigurationsdatei
- 4 Live Demo

Motivation

- (De)Aktivierung des Aufzeichnens von Methoden zur Laufzeit.
- Über Methoden in ProbeController.
- Über externe Konfigurationsdatei (ähnlich aop.xml).

Motivation

- (De)Aktivierung des Aufzeichnens von Methoden zur Laufzeit.
- Über Methoden in ProbeController.
- Über externe Konfigurationsdatei (ähnlich aop.xml).

Motivation

- (De)Aktivierung des Aufzeichnens von Methoden zur Laufzeit.
- Über Methoden in ProbeController.
- Über externe Konfigurationsdatei (ähnlich aop.xml).

Ansatz

- Liste von Pattern mit Signaturen vergleichen
- Idee: Code von aspectj wiederverwenden
- leider zu komplex
- Daher: Eigene Syntax und Implementierung

Ansatz

- Liste von Pattern mit Signaturen vergleichen
- Idee: Code von aspectj wiederverwenden
- leider zu komplex
- Daher: Eigene Syntax und Implementierung

Ansatz

- Liste von Pattern mit Signaturen vergleichen
- Idee: Code von aspectj wiederverwenden
- leider zu komplex
- Daher: Eigene Syntax und Implementierung

Ansatz

- Liste von Pattern mit Signaturen vergleichen
- Idee: Code von aspectj wiederverwenden
- leider zu komplex
- Daher: Eigene Syntax und Implementierung

Syntax

```
PATTERN = MODIFIER_CONSTRAINT_LIST RETURN_TYPE WS FQ_TYPE "." METHOD_NAME [WS] "(" [WS] [PARAM_LIST] [WS] ")" [WS]

WS = beliebiger whitespace
MODIFIER_CONSTRAINT_LIST =
    (("public" | "private" | "package" | "protected")WS)?(("static" | "non_static")WS)?(("native" | "non_native")WS)?
RETURN_TYPE = FQ_TYPE | "new"
FQ_TYPE = [FQ_PACKAGE "."] IDENTIFIER
FQ_PACKAGE = [".."] [IDENTIFIER ("." [".."] IDENTIFIER)* [".."]]
IDENTIFIER = (alpha|"*")(alpha|num|"*"*)*
PARAM_LIST = (".." | FQ_TYPE) ([WS] "," [WS] (".." | FQ_TYPE))*
METHOD_NAME = IDENTIFIER
```

- *
- ..* ..*.*(..)
- public non_static ..* package..Class.get*()
- int ..*.*(..)

Syntax

```
PATTERN = MODIFIER_CONSTRAINT_LIST RETURN_TYPE WS FQ_TYPE "." METHOD_NAME [WS] "(" [WS] [PARAM_LIST] [WS] ")" [WS]

WS = beliebiger whitespace
MODIFIER_CONSTRAINT_LIST =
    (("public" | "private" | "package" | "protected")WS)?(("static" | "non_static")WS)?(("native" | "non_native")WS)?
RETURN_TYPE = FQ_TYPE | "new"
FQ_TYPE = [FQ_PACKAGE "."] IDENTIFIER
FQ_PACKAGE = [".."] [IDENTIFIER ("." [".."] IDENTIFIER)* [".."]]
IDENTIFIER = (alpha|"*")(alpha|num|"*")*
PARAM_LIST = (".." | FQ_TYPE) ([WS] "," [WS] (".." | FQ_TYPE))*
METHOD_NAME = IDENTIFIER
```

- *
- ..* ..*.*(..)
- public non_static ..* package..Class.get*()
- int ..*.*(..)

Syntax

```

PATTERN = MODIFIER_CONSTRAINT_LIST RETURN_TYPE WS FQ_TYPE "." METHOD_NAME [WS] "(" [WS] [PARAM_LIST] [WS] ")" [WS]

WS = beliebiger whitespace
MODIFIER_CONSTRAINT_LIST =
  (("public" | "private" | "package" | "protected")WS)?(("static" | "non_static")WS)?(("native" | "non_native")WS)?
RETURN_TYPE = FQ_TYPE | "new"
FQ_TYPE = [FQ_PACKAGE "."] IDENTIFIER
FQ_PACKAGE = [".."] [IDENTIFIER ("." [".."] IDENTIFIER)* [".."]]
IDENTIFIER = (alpha|"*")(alpha|num|"*"*)*
PARAM_LIST = (".." | FQ_TYPE) ([WS] "," [WS] (".." | FQ_TYPE))*
METHOD_NAME = IDENTIFIER

```

- *
- `..* ..*.*(..)`
- `public non_static ..* package..Class.get*()`
- `int ..*.*(..)`

Syntax

```
PATTERN = MODIFIER_CONSTRAINT_LIST RETURN_TYPE WS FQ_TYPE "." METHOD_NAME [WS] "(" [WS] [PARAM_LIST] [WS] ")" [WS]

WS = beliebiger whitespace
MODIFIER_CONSTRAINT_LIST =
    (("public" | "private" | "package" | "protected")WS)?(("static" | "non_static")WS)?(("native" | "non_native")WS)?
RETURN_TYPE = FQ_TYPE | "new"
FQ_TYPE = [FQ_PACKAGE "."] IDENTIFIER
FQ_PACKAGE = [".."] [IDENTIFIER ("." [".."] IDENTIFIER)* [".."]]
IDENTIFIER = (alpha|"*")(alpha|num|"*")*
PARAM_LIST = (".." | FQ_TYPE) ([WS] "," [WS] (".." | FQ_TYPE))*
METHOD_NAME = IDENTIFIER
```

- *
- `..* ..*.*(..)`
- `public non_static ..* package..Class.get*()`
- `int ..*.*(..)`

Syntax

```
PATTERN = MODIFIER_CONSTRAINT_LIST RETURN_TYPE WS FQ_TYPE "." METHOD_NAME [WS] "(" [WS] [PARAM_LIST] [WS] ")" [WS]

WS = beliebiger whitespace
MODIFIER_CONSTRAINT_LIST =
    (("public" | "private" | "package" | "protected")WS)?(("static" | "non_static")WS)?(("native" | "non_native")WS)?
RETURN_TYPE = FQ_TYPE | "new"
FQ_TYPE = [FQ_PACKAGE "."] IDENTIFIER
FQ_PACKAGE = [".."] [IDENTIFIER ("." [".."] IDENTIFIER)* [".."]]
IDENTIFIER = (alpha|"*")(alpha|num|"*"*)*
PARAM_LIST = (".." | FQ_TYPE) ([WS] "," [WS] (".." | FQ_TYPE))*
METHOD_NAME = IDENTIFIER
```

- *
- ..* ..*.*(..)
- public non_static ..* package..Class.get*()
- int ..*.*(..)

Gliederung

- 1 Einleitung
 - Motivation
 - Ansatz
 - Syntax
- 2 ProbeController
 - API
 - ProbeController
- 3 Konfiguration über Datei
 - Kieker Properties
 - Konfigurationsdatei
- 4 Live Demo

IProbeController

[Package](#) [Class](#) [Use](#) [Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV CLASS](#) [NEXT CLASS](#)
[SUMMARY](#) | [NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#)

[FRAMES](#) [NO FRAMES](#)
[DETAIL](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#)

kieker.monitoring.core.controller

Interface IProbeController

```
public interface IProbeController
```

Author:

Jan Waller, Bjoern Weissenfels

Method Summary

boolean	activateProbe (java.lang.String pattern) Activates a probe.
boolean	deactivateProbe (java.lang.String pattern) Deactivates a probe.
boolean	isProbeActivated (java.lang.String signature) Checks whether a probe is active.
void	replaceProbePatternList (java.util.List<kieker.monitoring.core.signaturePattern.PatternEntry> patternList) Replaces the existing activity rules with new ones that are defined in patternList.

ProbeController

```
Java EE - kieker/src/monitoring/kieker/monitoring/core/controller/ProbeController.java - Eclipse
File Edit Run Source Navigate Search Project Refactor Window Help
ProbeController.java FileWatcher.java PatternEntry.java IProbeController.java
2* * Copyright 2012 Kieker Project (http://kieker-monitoring.net)
16
17 package kieker.monitoring.core.controller;
18
19 import java.io.BufferedReader;
45
47* * @author Jan Waller, Bjoern Weissenfels
49 public class ProbeController extends AbstractController implements IProbeController {
50     private static final Log LOG = LoggerFactory.getLog(ProbeController.class);
51     private static final PatternEntry defaultPattern = new PatternEntry("", PatternParser.parseToPattern("", true);
52
53     private final String configFilepathname;
54     private final long configFileReadIntervall;
55     private final boolean configFileUpdate;
56
57     private final ConcurrentMap<String, Boolean> signatureCache = new ConcurrentHashMap<String, Boolean>();
58     private final CopyOnWriteArrayList<PatternEntry> patternList = new CopyOnWriteArrayList<PatternEntry>();
59
60     private FileWatcher fileWatcher;
61     private File file;
62
63* protected ProbeController(final Configuration configuration) {}
69
71* protected void init() {}
107
108* private List<PatternEntry> readInputStream(final InputStream inputStream) throws IOException {}
135
137* protected void cleanup() {}
143
145* public String toString() {}
160
161* public boolean activateProbe(final String pattern) {}
164
165* public boolean deactivateProbe(final String pattern) {}
168
```



Gliederung

- 1 Einleitung
 - Motivation
 - Ansatz
 - Syntax
- 2 ProbeController
 - API
 - ProbeController
- 3 Konfiguration über Datei
 - Kieker Properties
 - Konfigurationsdatei
- 4 Live Demo

Kieker Properties

```
63 #####
64 ##### PROBECONTROLLER #####
65 #####
66 ## Default location of the adaptive monitoring configuration File
67 kieker.monitoring.adaptiveMonitoring.configFile=META-INF/kieker.monitoring.adaptiveMonitoring.configFile
68
69 ## Enable/disable the updating of the pattern file by activating or deactivating probes through jmx.
70 kieker.monitoring.adaptiveMonitoring.updateConfigFile=true
71
72 ## The delay in seconds in which the pattern file is checked for changes.
73 ## 0 to disable the observation.
74 kieker.monitoring.adaptiveMonitoring.readInterval=10
```

Konfigurationsdatei

```
Syntax.txt kieker.monitoring.adaptiveMonitoring.configFile
1 # a comment starts with '#' and will be ignored
2 # an include pattern starts with '+' and an exclude pattern with '-'
3 # every other line results in a warning
4 - ..* ..MonitoredClass.*(..)
5 + private static void ..*.*(..)
6 - public java.util.List ..*.*(..)
7 + public ..* ..*.*()
8 - public int evaluation.monitoredApplication.MonitoredClass.get*()
```

Gliederung

- 1 Einleitung
 - Motivation
 - Ansatz
 - Syntax
- 2 ProbeController
 - API
 - ProbeController
- 3 Konfiguration über Datei
 - Kieker Properties
 - Konfigurationsdatei
- 4 Live Demo